Date Printed: 08/16/2021 Product #3301 - A



Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier #3301 A Revision Date: 08/16/2021

Product Name: Epoxy.com Product #3301 Part A Supercedes Date: 08/16/2021

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Epoxy Systems, Inc DBA

Epoxy.com

20774 W. Pennsylvania Ave Dunnellon, FL 34431 sales@epoxy.com www.epoxy.com Tel: (352) 489-1666

Fax: (352) 489-1625

Datasheet Produced by: Lambert, Norm norm@epoxy.com

1.4 Emergency telephone number: PERS (USA) 800-633-8253 – (International) +1 (801) 629-0667.

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Serious Eye Damage, category 1 Skin Irritation, category 2 Skin Sensitizer, category 1 Date Printed: 08/16/2021 Product: #3301 - A

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

cashew nutshell oil, Trimethylolpropane triacrylate, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Causes skin irritation.

Collect spillage.

May cause an allergic skin reaction.

H315

H317

HAZARD STATEMENTS Skin Irritation, category 2

Skin Sensitizer, category 1

| Serious Eye Damage, category 1 | H318 | Causes serious eye damage. |
|---|--------------|---|
| Hazardous to the aquatic environment, Chronic, category 2 | H411 | Toxic to aquatic life with long lasting effects. |
| PRECAUTION PHRASES | | |
| | P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| | P273 | Avoid release to the environment. |
| | P280 | Wear protective gloves/protective clothing/eye protection/ face protection. |
| | P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| | P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| | P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
| | P333+313 | If skin irritation or rash occurs: Get medical advice/attention. |

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P391

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

| CAS-No. | Chemical Name | <u>%</u> |
|------------|---|----------|
| 25068-38-6 | Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 75-95 |
| 68609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 2.5-10 |
| 8007-24-7 | cashew nutshell oil | 2.5-10 |
| 15625-89-5 | Trimethylolpropane triacrylate | 1.0-2.5 |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | 0.1-1.0 |
| 108-83-8 | 2.6-dimethylheptan-4-one | 0.1-1.0 |
| 108-88-3 | Toluene | <0.1 |

| CAS-No. | GHS Symbols | GHS Hazard Statements | M-Factors |
|------------|-------------|-----------------------|-----------|
| 25068-38-6 | GHS07-GHS09 | H315-317-319-411 | 0 |
| 68609-97-2 | GHS07 | H315-317 | 0 |

Date Printed: 08/16/2021 Product: #3301-A

| 8007-24-7 | GHS05-GHS07 | H302-312-315-317-318 | 0 |
|------------|-------------------|--------------------------|---|
| 15625-89-5 | GHS07 | H315-317-319 | 0 |
| 64742-47-8 | GHS07-GHS08-GHS09 | H304-336-411 | 0 |
| 108-83-8 | GHS02-GHS07 | H226-332-335-336 | 0 |
| 108-88-3 | GHS02-GHS07-GHS08 | H225-304-315-336-361-373 | 0 |

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Date Printed: 08/16/2021 Product: #3301 A

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

| Name | CAS-No. | OSHAPEL | ACGIH TLV |
|--|------------|-----------|-----------|
| Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 25068-38-6 | | |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 68609-97-2 | | |
| cashew nutshell oil | 8007-24-7 | | |
| Trimethylolpropane triacrylate | 15625-89-5 | | |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | 500.0 PPM | 100.0 PPM |
| 2,6-dimethylheptan-4-one | 108-83-8 | 50.0 PPM | 25.0 PPM |
| Toluene | 108-88-3 | 100.0 PPM | 50.0 PPM |

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Transparent resin

Physical State Liquid

Date Printed: 08/16/2021 Product: 3301 - A

Odor Weak epoxy

Odor threshold Not determined

pH Non-aqueous

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 111 - N.D.

Flash Point, (°F / °C) >200 F

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 999 - 0

limits

Vapour Pressure Not determined

Vapour density 1.16 g/cm3

Relative density Not determined

Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Not determined

Not determined

Not determined

Explosive properties N/A

Oxidising properties N/A

9.2 Other information

VOC Content g/l: 20

Density (lbs./gal) 9.08

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

Date Printed: 08/16/2021 Product: #3301 - A

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: Irritating to eyes, skin, mouth and pharynx.

Corrosivity: No information available.

Sensitization: Prolonged or repeated skin contact may result in allergic eczema.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|--|--|------------------|-----------------------------------|
| 25068-38-6 | Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700) | >2000 mg/kg, rat, oral | >2000 mg/kg, rat | |
| 68609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 17100 mg/kg, oral, rat | | |
| 15625-89-5 | Trimethylolpropane triacrylate | 5000 mg/kg, oral, rat | | |
| 108-83-8 | 2,6-dimethylheptan-4-one | 3200 mg/kg, oral, rat | | 1979 ppm / 6 hrs, rat, inhalation |
| 108-88-3 | Toluene | 5000 mg/kg rat oral, 14000 mg/kg rabbit dermal | | 8000 ppm/4 hrs, rat, inhalation |

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

Date Printed: 08/16/2021 Product: 3301 - A

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

| CAS-No. | Chemical Name | EC50 48hr | IC50 72hr | LC50 96hr |
|------------|--|----------------|----------------|-----------|
| 25068-38-6 | Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700) | No information | No information | |
| 68609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | No information | No information | |
| 8007-24-7 | cashew nutshell oil | No information | No information | |
| 15625-89-5 | Trimethylolpropane triacrylate | No information | No information | |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | No information | No information | |
| 108-83-8 | 2,6-dimethylheptan-4-one | No information | No information | |
| 108-88-3 | Toluene | No information | No information | |

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

| 14.1 | UN number | UN3082 |
|------|-----------|--------|
| | | |

14.2 UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S.

Technical name (Epoxy Resin)

14.3 Transport hazard class(es) 9
Subsidiary shipping hazard N/A

14.4 Packing group14.5 Environmental hazardsYes

14.6 Special precautions for userNot applicable
EmS-No.:
F-A, S-F

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation

Date Printed: 08/16/2021 Product: 3301 -A

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.

 Xylene
 1330-20-7

 Ethylbenzene
 100-41-4

 Cumene
 98-82-8

 Toluene
 108-88-3

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category: Floor Coatings

EPA VOC Content Limit (g/l): 400
Product VOC Content (g/l) <20
Thinning Recommendations: None

Application Recommendations: For professional use only.

- * As per the federal EPA definition for coating categories in 40 CFR 59.401.
- ** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

Date Printed: 08/16/2021 Product: 3301-A

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 02 - Hazard Identification

UZ - MAZAIU IUENCIIICACION

This is a new Safety Data Sheet (SDS).

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OCL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

OSHA American Conference of Governmental Industrial Hygienists

PEL Occupational Safety & Health Administration

 $\begin{array}{ccc} \text{VOC} & \text{Permissible Exposure Limits} \\ \text{q/l} & \text{Volatile organic compounds} \end{array}$

mg/kg Grams per liter

N/A Milligrams per kilogram

LD50 Not applicable LC50 Lethal dose at 50%

EC50 Lethal concentration at 50%

IC50 Half maximal effective concentration Half

PBT maximal inhibitory concentration

vPvB Persistent bioaccumulative toxic chemical

Very persistent and very bioaccumulative

Date Printed: 08/16/2021 Product: #3301 -A

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG
IATA
International Maritime Dangerous Goods Code
IATA
International Air Transport Association
MARPOL

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

RTI International Bulk Container
NE Respiratory Tract Irritation

Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.