# MATERIAL SAFETY DATA SHEET EPOXY.COM RESIN SELF LEVELING FILLER

PRODUCT NAME: EPOXY.COM #7 PRODUCT CODE:	8 SELF-LEVELING FILLER	HMIS CODES:	H F R M 2 0 0 E		
DOT Shipping Identification: DOT Hazard Class:	Non flammable so UN/NA not listed	lid			
SECTION 1: MANUFACTURER IDENTIFICATION   MANUFACTURER'S NAME: EPOXY SYSTEMS, INC.   ADDRESS: 20774 West Pennsylvania Ave.   Dunnellon, FI 34431					
	633-8253 489-1666	DATE PRINTED NAME OF PREI	-	05/20/10 K. Fontaine	
SECTION 2: INGREDIENTS					
ITEM	CAS NUMBER	OSHA-PEL	ACGIH-TLV		
Silica Sand	14808-60-7	0.1 mg/m <sup>3</sup>		(IARC-Limited Evidence)	

Substances listed are present in concentration of 1% or greater, or if 0.01% if cited as a potential carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

# SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE	: N/A
VAPOR DENSITY	: N/A
VAPOR PRESSURE	: N/A
SOLUBILITY IN WATER	: NIL
APPEARANCE AND ODOR	: GRAINY SOLID
SPECIFIC GRAVITY (H20=1)	: 2.6
ODOR	: NONE

# SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A EXTINGUISHING MEDIA: NONE SPECIAL FIRE FIGHTING PROCEDURES: Wear protective pressure self contained breathing apparatus because of microcrystalline dust exposure. UNUSUAL HAZARDS: None

# **SECTION 5: REACTIVITY DATA**

STABILITY: STABLE CONDITIONS TO AVOID:

# SECTION 6: HEALTH HAZARD DATA

SYMPTOMS OF EXPOSURE:

EYES: may irritate

SKIN: Not likely to occur

INHALATION: non-toxic, but excessive exposure can cause delayed lung damage (Silicosis) INGESTION: Not likely to occur

# FIRST AID PROCEDURES:

EYES: Flush with water. Get medical attention if irritation persists. SKIN: Wash with soap and water. INGESTION: INHALATION: Remove to fresh air.

### SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL/LEAK: Sweep up and dispose of in sanitary land fill.

#### **SECTION 8: CONTROL MEASURES**

Wear appropriate clothing to minimize skin contact and abrasion. Wear safety glasses or goggles. Wear dust mask when handling.

### **SECTION 9: ADDITIONAL INFORMATION**

Grinding or abrasive action to cured product containing self-leveling filler can generate microcrystalline dust. Wear a dust mask.